HUAHE®

中国·华和重工有限公司
CHINA · HUAHE HEAVY INDUSTRIES CO.,LTD

地址:中国浙江省台州市路桥区金清镇沥北村
ADD:Libei Village,Jinqing Town,Luqiao District,Taizhou City,Zhejiang Province,china
客服热线(Hotline):967967　4008 812 444
电话(Tel):+86-576-8270 1111　8271 3334　8271 3329
传真(Fax):+86-576-8201 1111　8271 0298
www.chinahuahe.com
Http://huahe.en.alibaba.com
E-mail:sales@chinahuahe.com / joy@chinahuahe.com

SONCAP EPA



GASOLINE GENERATOR

HH3700-G/HH2500-A05





HH3700-G/HH2500-A05					
GENERATOR	Rated Power Output/W	2000W	2500W	2800W	3000W
	Max Power Output/W	2200W	2700W	3000W	3300W
	Rated Voltage/V	220V/380V	220V/380V	220V/380V	2220V/380V
	Rated Current	9.1A	11.4A	12.7A	13.6A
	Frequency/Hz	50Hz	50Hz	50Hz	50Hz
	Model	168	168F	170F	172F
ENGINE	Type	Single cylinder,4-stroke	Single cylinder,4-stroke	Single cylinder,4-stroke	Single cylinder,4-stroke
	Displacement	163cc	196cc	212cc	223cc
	Max output	5.5HP	6.5HP	7.0HP	7.5HP
	Fuel	Gasoline	Gasoline	Gasoline	Gasoline
	Fuel tank	15L	15L	15L	15L
WHOLE	Starting system	Recoil/Electric	Recoil/Electric	Recoil/Electric	Recoil/Electric
	Noise level (at 7m)	95dB	96dB	96dB	96dB
	HH3700-G Dimension (L×W×H)	470x385x500mm	470x385x500mm	470x385x500mm	470x385x500mm
	HH2500-A05 Dimension (L×W×H)	605x430x435mm	605x430x435mm	605x430x435mm	605x430x435mm
	G.W.	36kg	38kg	39kg	40kg

DIGITAL INVERTER GENERATOR

Hi4500-K



OPTIONAL FUNCTION:





Hi4500-K		
GENERATOR	Rated power output/W	3000W/3500W/4000W/4800W
	Max power output/W	3200W/3800W/4200W/5000W
	Rated voltage/V	230V/110V
	Frequency/Hz	50Hz/60Hz
	Power factor	1.0
	Waveform distortion rate/%	⩽3%
	Noise level (at 7m)	⩽97dB
	Overload protection AC	Frequency converter overcurrent protection program control
	Operating Altitude	⩽1000m
ENGINE	Engine Model	HH170F/HH172F
	Engine Type	Single cylinder,Four stroke,Forced air cooling,Overhead valve
	Displacement (cc)	223cc/240cc
	Fuel Type	Unleaded gasoline
	Fuel tank capacity	8L
	Engine oil volume	0.6L
OVERALL DIMENSIONS	Ignition plug model	F7RTC/FTTC
	Starting system	Manual start
	L×W×H/mm	475x390x500mm
	Net weight	24.5kg

DIGITAL WELDING GENERATOR

Hi4500W-PRO



OPTIONAL FUNCTION:





Hi4500W-PRO		
GENERATOR	Rated power output/W	3000W
	Max power output/W	3200W
	Rated voltage/V	230V/110V
	Frequency/Hz	50Hz/60Hz
	Power factor	1.0
	Waveform distortion rate/%	⩽3%
	Noise level (at 7m)	⩽97dB
	Operload protection AC	Frequency converter overcurrent protection program control
	Operating Altitude	⩽1000m
ENGINE	Engine Model	HH170F
	Engine Type	Single cylinder,Four stroke,Forced air cooling,Overhead valve
	Displacement (cc)	212cc
	Fuel Type	Unleaded gasoline
	Fuel tank capacity	8L
	Engine oil volume	0.6L
WELDER	Rated current	130A / 160A
	Max current	160A / 190A
OVERALL DIMENSIONS	Ignition plug model	F7RTC / FTTC
	Starting system	Manual start
	L×W×H/mm	470x380x720mm
	Net weight	25kg

DIGITAL INVERTER GENERATOR

Hi7500D/Hi8500D/Hi9500D



OPTIONAL FUNCTION:





		Hi7500D	Hi8500D	Hi9500D
GENERATOR	Frequency/Hz	50Hz/60Hz		
	Rated voltage/V	230V/110V/380V		
	Rated power output/W	7000W	8000W	9000W
	Max power output/W	7500W	8500W	9500W
	Power factor	1.0		
	Waveform distortion rate/%	⩽3%		
	Noise level (at 7m)	⩽97dB		
	Overload protection AC	Frequency converter overcurrent protection program control		
	Operating Altitude	⩽1000m		
ENGINE	Engine Model	HH190F	HH192F	HH194
	Engine Type	Single cylinder,Four stroke,Forced air cooling,Overhead valve		
	Displacement (cc)	420cc	460cc	500cc
	Fuel Type	Unleaded gasoline		
	Fuel tank capacity	25L		
	Engine oil volume	1.1L		
OVERALL DIMENSIONS	Ignition plug model	F7RTC/FTTC		
	Starting system	Manual start/Electric start		
	L×W×H/mm	640x540x655mm		
	Net weight	65-70kg		

DIGITAL INVERTER GENERATOR

Hi7500EB/Hi9500EB/Hi12500EB



OPTIONAL FUNCTION:

USB | DIGITAL DISPLAYER | E-START | DUAL FUEL LPG | PARALLEL

	Hi7500EB/Hi9500EB/Hi12500EB	
GENERATOR	Rated power output/W	7000W/9000W/11000W
	Max power output/W	7500W/9500W/12000W
	Rated voltage/V	230V/110V/380V
	Frequency/Hz	50Hz/60Hz
	Power factor	1
	Waveform distortion rate/%	⩽3%
	Noise level(at 7m)	⩽97dB
	Overload protection AC	Frequency converter overcurrent protection program control
	Operating Altitude	⩽1000m
	Engine Model	HH190F/HH192F/HH194
ENGINE	Engine Type	Single cylinder, Four stroke, Forced air cooling, Overhead valve
	Displacement(cc)	420cc/460cc/500cc
	Fuel Type	Unleaded gasoline
	Fuel tank capacity	25L
	Engine oil volume	1.1L
WHOLE	Ignition plug model	F7RTC/FTTC
	Starting system	Electric start
	L x W x H/mm	605x525x625mm
	Net weight	60kg/65kg/75kg



HIGH PRESSURE WASHER

HHPW170X



5PCS NOZZLE



1PC HIGH PRESSURE HOSE 8M



1PC INLET PIPE



	HHPW170X	
Horse power	5.5HP	6.5HP
Flow	7.5(L/min)	9.2(L/min)
Rated Pressure	14Mpa(2000psi)	17Mpa(2465psi)
Max Pressure	16Mpa(2300psi)	20Mpa(2900psi)
Displacement	163cc	196cc
Pump type	Axial pump	Axial pump
Engine type	HH168	HH168F
Engine speed	3600(RPM)	3600(RPM)
Ambient	0℃-60℃	0℃-60℃
Engine oil capacity	0.6L	0.6L
Fuel tank capacity	3.6L	3.6L
Fuel Type	Gasoline	Gasoline
Gross Weight	28kg	29kg
Dimension	515x370x580mm	515x370x580mm



DIGITAL INVERTER GENERATOR

HH1500IS

OPTIONAL FUNCTION:

USB | DIGITAL DISPLAYER | DUAL FUEL LPG | PARALLEL





HH1500IS	
Max Power Output	1100W
Continuous Power Output	1000W
Voltage Control	Digital Inverter
Rated Voltage	220V/110V
Frequency	50Hz/60Hz
Nominal Current Rating	4.3A
Motor Power	max.1.5kW(2.04HP)
Engine Capacity	approx.56cm³
Fuel Consumption	approx.0.65L/hr(with 2/3 load)
Fuel Tank Volume	approx.3L
Fuel	regular and premium petrol

DIGITAL INVERTER GENERATOR

Hi1800S







Hi1800S		
GENERATOR	Rated power output/W	1000W
	Max power output/W	1020W
	Rated voltage/V	220V
	Frequency/Hz	50Hz
	Power factor	1.0
	Waveform distortion rate/%	⩽3%
	Noise level (at 7m)	⩽90dB
	Overload protection AC	Frequency converter overcurrent protection program control
	Operating Altitude	⩽1000m
ENGINE	Engine Model	HH144
	Engine Type	Single cylinder,Four stroke,Forced air cooling,Overhead valve
	Displacement (cc)	53.5cc
	Fuel Type	Regular and premium petrol
	Fuel tank capacity	4.5L
	Engine oil volume	0.6L
OVERALL DIMENSIONS	Ignition plug model	F7RTC/FTTC
	Starting system	Manual start
	L×W×H/mm	420x320x398mm
	Net weight	14kg

DIGITAL INVERTER GENERATOR

Hi2800S





Hi2800S		
GENERATOR	Rated power output/W	2000W
	Max power output/W	2050W
	Rated voltage/V	220V
	Frequency/Hz	50Hz
	Power factor	1.0
	Waveform distortion rate/%	⩽3%
	Noise level (at 7m)	⩽90dB
	Overload protection AC	Frequency converter overcurrent protection program control
	Operating Altitude	⩽1000m
ENGINE	Engine Model	HH148
	Engine Type	Single cylinder,Four stroke,Forced air cooling,Overhead valve
	Displacement (cc)	79.8cc
	Fuel Type	Regular and premium petrol
	Fuel tank capacity	4.5L
	Engine oil volume	0.6L
OVERALL DIMENSIONS	Ignition plug model	F7RTC/FTTC
	Starting system	Manual start
	L×W×H/mm	465x310x470mm
	Net weight	20.5kg

DIGITAL INVERTER GENERATOR

Hi3800S





Hi3800S		
GENERATOR	Rated power output/W	3000W
	Max power output/W	3200W
	Rated voltage/V	230V/110V
	Frequency/Hz	50Hz/60Hz
	Power factor	1.0
	Waveform distortion rate/%	⩽3%
	Noise level (at 7m)	⩽90dB
	Overload protection AC	Frequency converter overcurrent protection program control
	Operating Altitude	⩽1000m
ENGINE	Engine Model	HH165
	Engine Type	Single cylinder,Four stroke,Forced air cooling,Overhead valve
	Displacement (cc)	149cc
	Fuel Type	Unleaded gasoline
	Fuel tank capacity	5L
	Engine oil volume	0.6L
OVERALL DIMENSIONS	Ignition plug model	F7RTC/FTTC
	Starting system	Manual start
	L×W×H/mm	520x325x495mm
	Net weight	20.5kg